



KEMgage - a manual shrinkage control unit for both, 35 and 16mm stock

A handy and helpful table-top device with an utmost gentle film insertion ruler of the inserted 10.5 (35mm) or 26 (16mm) frames and direct reading of the longitudinal shrinkage-values over this distance

A stable and proven mechanical system for the careful work with any type of stock in film archives

KEM gage



Key Features

- Long- lasting mechanical gauge
- 35/16mm (two measuring modes)
- Firm and stable
- Film thread from left to right
- Peli Case with foam interior included
- Recalibration after battery change
- Calibrated ex works
- Battery life approx. 7000h
- No lubrication is needed



KEMgage, the proven film shrinkage gauge of KEM K-SG16/35, with its functional and simple mechanical design as well as direct reading of percentage values on the LCD digital display, a helpful assist that allows you to keep the control over the measurement process at a glance and treat the stock as gentle as possible. It comes with a practical soft foamed Peli Case for both: safe transport and storage of your measurement



Technical Details

Measurement distance film:	199.5mm
At 35mm:	10.5 frames
At 16mm:	26 frames
Gauging force:	< 0.5N (< 50g)
Measuring range:	max. 3.5%
Dial gauge:	Mitutoyo Digimatic
Measuring range of dial gauge:	12.7mm
Resolution:	0.01mm
Repeat accuracy:	0.01mm
Battery:	SR44 silver oxide battery
Surround conditions:	temp: 59° - 104°F (15° - 40°C) 35% - 65% rel. humidity non-condensing
Dimensions Peli-Case (L*W*H):	11.65" x 8.35" x 3.78" (29.6 x 21.2 x 9.6 cm)
Weight (incl. case):	approx. 4.4lbs (2kg)

Distributed by: